


# Absolyte 3-100G13 data sheet

ABSOLYTE™



Terminal:



Meets: UL94 V0

## Specifications:

Exide type designation	Part number	Nom. Voltage V	Nominal capacity C <sub>8</sub> 1.75 Vpc 25°C Ah	Length l max. mm	Width b/w max. mm	Height h1 max. mm	Weight approx. kg	Terminal
3-100G13	NAGP060600HA0FA	6	600	506.0	217.0	670.0	149.490	F-M6

Part numbers not valid for North America, use type for ordering!

## Constant-current discharge in A (@ 25 °C):

Part number	Exide type designation	VpC	15min	30min	1h	2h	3h	4h	5h	8h	10h
NAGP060600HA0FA	100A13	1.94			182.0	135.0	107.0	88.0	75.0	55.0	47.0
NAGP060600HA0FA	100A13	1.92			206.0	148.0	116.0	96.0	81.0	59.0	50.0
NAGP060600HA0FA	100A13	1.90			228.0	161.0	126.0	103.0	87.0	63.0	54.0
NAGP060600HA0FA	100A13	1.88			246.0	172.0	133.0	109.0	92.0	67.0	56.0
NAGP060600HA0FA	100A13	1.86			265.0	181.0	141.0	115.0	98.0	70.0	59.0
NAGP060600HA0FA	100A13	1.84			279.0	191.0	148.0	119.0	100.0	72.0	60.0
NAGP060600HA0FA	100A13	1.83			286.0	195.0	151.0	121.0	102.0	72.0	61.0
NAGP060600HA0FA	100A13	1.81	478.0	397.0	298.0	201.0	155.0	123.0	104.0	73.0	61.0
NAGP060600HA0FA	100A13	1.80	492.0	406.0	301.0	201.0	156.0	124.0	105.0	73.0	62.0
NAGP060600HA0FA	100A13	1.78	522.0	421.0	306.0	207.0	157.0	126.0	106.0	73.0	62.0
NAGP060600HA0FA	100A13	1.75	559.0	446.0	312.0	212.0	158.0	128.0	107.0	75.0	62.0