


Absolyte 6-90G13 data sheet

ABSOLYTE™



Terminal:



Meets: UL94 V0

Specifications:

Exide type designation	Part number	Nom. Voltage V	Nominal capacity C ₈ 1.75 Vpc 25°C Ah	Length l max. mm	Width b/w max. mm	Height h1 max. mm	Weight approx. kg	Terminal
6-90G13	NAGP120520HA0FA	12	520	894.0	217.0	599.0	253.490	F-M6

Part numbers not valid for North America, use type for ordering!

Constant-current discharge in A (@ 25 °C):

Part number	Exide type designation	VpC	15min	30min	1h	2h	3h	4h	5h	8h	10h
NAGP120520HA0FA	90A13	1.94			182.0	126.0	98.0	82.0	70.0	52.0	43.0
NAGP120520HA0FA	90A13	1.92			198.0	137.0	106.0	89.0	75.0	55.0	46.0
NAGP120520HA0FA	90A13	1.90			210.0	147.0	113.0	93.0	79.0	57.0	48.0
NAGP120520HA0FA	90A13	1.88			230.0	153.0	119.0	97.0	82.0	60.0	50.0
NAGP120520HA0FA	90A13	1.86			246.0	161.0	124.0	103.0	87.0	61.0	52.0
NAGP120520HA0FA	90A13	1.84			258.0	168.0	127.0	103.0	87.0	62.0	53.0
NAGP120520HA0FA	90A13	1.83			263.0	170.0	129.0	105.0	89.0	62.0	53.0
NAGP120520HA0FA	90A13	1.81	448.0	375.0	276.0	175.0	131.0	107.0	91.0	64.0	54.0
NAGP120520HA0FA	90A13	1.80	461.0	385.0	283.0	177.0	132.0	106.0	91.0	64.0	54.0
NAGP120520HA0FA	90A13	1.78	489.0	401.0	290.0	181.0	135.0	109.0	93.0	65.0	55.0
NAGP120520HA0FA	90A13	1.75	529.0	428.0	302.0	186.0	138.0	111.0	94.0	65.0	55.0