


Absolyte 6-90G15 data sheet

ABSOLYTE™



Terminal:



Meets: UL94 V0

Specifications:

| Exide type designation | Part number | Nom. Voltage V | Nominal capacity C ₈ 1.75 Vpc 25°C Ah | Length l max. mm | Width b/w max. mm | Height h1 max. mm | Weight approx. kg | Terminal |
|------------------------|-----------------|----------------|--|------------------|-------------------|-------------------|-------------------|----------|
| 6-90G15 | NAGP120608HA0FA | 12 | 608 | 1,008.0 | 218.0 | 599.0 | 289.490 | F-M6 |

Part numbers not valid for North America, use type for ordering!

Constant-current discharge in A (@ 25 °C):

| Part number | Exide type designation | VpC | 15min | 30min | 1h | 2h | 3h | 4h | 5h | 8h | 10h |
|-----------------|------------------------|------|-------|-------|-------|-------|-------|-------|-------|------|------|
| NAGP120608HA0FA | 90A15 | 1.94 | | | 212.0 | 147.0 | 115.0 | 96.0 | 81.0 | 60.0 | 50.0 |
| NAGP120608HA0FA | 90A15 | 1.92 | | | 231.0 | 160.0 | 124.0 | 103.0 | 88.0 | 64.0 | 54.0 |
| NAGP120608HA0FA | 90A15 | 1.90 | | | 245.0 | 172.0 | 132.0 | 109.0 | 93.0 | 67.0 | 56.0 |
| NAGP120608HA0FA | 90A15 | 1.88 | | | 269.0 | 178.0 | 138.0 | 113.0 | 96.0 | 70.0 | 58.0 |
| NAGP120608HA0FA | 90A15 | 1.86 | | | 287.0 | 188.0 | 144.0 | 120.0 | 101.0 | 71.0 | 61.0 |
| NAGP120608HA0FA | 90A15 | 1.84 | | | 301.0 | 196.0 | 148.0 | 120.0 | 102.0 | 72.0 | 62.0 |
| NAGP120608HA0FA | 90A15 | 1.83 | | | 307.0 | 199.0 | 151.0 | 123.0 | 104.0 | 72.0 | 62.0 |
| NAGP120608HA0FA | 90A15 | 1.81 | 522.0 | 437.0 | 322.0 | 204.0 | 153.0 | 125.0 | 106.0 | 74.0 | 63.0 |
| NAGP120608HA0FA | 90A15 | 1.80 | 538.0 | 449.0 | 331.0 | 206.0 | 154.0 | 124.0 | 107.0 | 75.0 | 63.0 |
| NAGP120608HA0FA | 90A15 | 1.78 | 571.0 | 468.0 | 338.0 | 212.0 | 157.0 | 127.0 | 109.0 | 76.0 | 64.0 |
| NAGP120608HA0FA | 90A15 | 1.75 | 618.0 | 499.0 | 352.0 | 217.0 | 162.0 | 130.0 | 110.0 | 76.0 | 64.0 |