



by Schneider Electric

List Price \$27.30 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.**

Technical Characteristics

Range on Increasing Pressure	20 to 65 PSIG
Action	Standard Action
Application	To control electrically driven water pumps
Actuator Type	Diaphragm
Contact Arrangement	DPST
Enclosure Rating	NEMA 1
Flange Material	Zinc Plated Steel
Depth	2.78 Inches
Approvals	UL Listed File: E12158 CCN NKPZ - CSA Certified File: LR25490
Marketing Trade Name	Pumptrol
Diaphragm	Nitrile (Buna N)
Differential	15 to 30 PSIG
Enclosure Type	General Purpose (Indoor)
Differential Type	Adjustable
Height	2.80 Inches
Maximum Voltage Rating	575VAC
Horsepower Rating (3-Phase)	2HP@115VAC - 3HP@230VAC - 1HP@460/575VAC
Horsepower Rating (1-Phase)	1.5HP@115VAC - 2HP@230VAC
Maximum Allowable Pressure	220 PSIG
Mounting Type	Bracket
Weight	1.13 Pounds
Number of Poles	2-Pole
Pressure Connection	0.25 Inch NPSF
Pressure Setting	30 to 50 PSIG
Range on Decreasing Pressure	10 to 45 PSIG
Terminal Type	Screw Clamp
Type	F
Width	3.76 Inches

Shipping and Ordering

Category	21534 - Pressure Switches, Commercial, Individual Pack, Type FSG, FYG, FSW, FYW & FRG
Discount Schedule	CP7I

Generated: 09/10/2012 12:28:55

GTIN	00785901077213
Package Quantity	50
Weight	0.87 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y
Country of Origin	MX

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.