

8G22NF

SPECIFICATIONS

Nominal Voltage (V)	12V
Capacity at C/100	58.2Ah
Capacity at C/20	50.9Ah
Weight	37 Lbs. (16.8 kg)
Plate Alloy	Lead Calcium
Posts	Forged terminals & bushings
Container/Cover	Polypropylene
Operating Temperature Range	-76°F (-60°C) – 140°F (60°C)
Charge Voltage @ 68°F (20°C)	
Cycle	2.30 - 2.35 VPC
Float	2.25 - 2.30 VPC
Vent	Self-sealing (2 PSI operation)
Electrolyte	Sulfuric acid thixotropic gel
Resistance	4.0 Milliohms (full charge)
Terminal	T881

Rated non-spillable by ICAO, IATA and DOT

Made in the U.S.A by East Penn Manufacturing

Distributed by:


Valve-Regulated, Gelled-Electrolyte Battery



DIMENSIONS

Length (mm)	9.38 (238 mm)
Width (mm)	5.50 (140 mm)
Height (mm)	9.25 (235 mm)

Gel Cycle Life vs Depth of Discharge at +25°C (77°F)
Based on BCI 2-hour Capacity



Cycle Chart applies to all MK Gel batteries (except 8GGC2 cycle chart x 2, 8G24/8G27 with a T872M terminal and 8G31DT cycle chart x .67).

MK Battery

1645 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-Mail: sales@mkbattery.com

